

Rimini Parasol Fabric collection 2018



SOLAR PROTECTION FACTOR

Harmful UV rays and limiting heat circulation
Norm UNI EN 410:2011



FACTOR OF SOLAR LIGHT PROTECTION%

of light transmission
Norm UNI EN 410:2011



UPF PROTECTION FACTOR

Harmful UV rays. (UPF) from 85% almost
100% Norm UNI EN 13758-1:2007

DATA SHEET

COMPOSITION

350 gr/m²
100% ACRYL

FINISHING

Resistant to mould and
bacteria. Colour fast.
Breathable.
Stain REPELLENT.

COLOUR FASTNESS

GRADE 7/8
ENSIO 105-B04

TREATMENT

TEFLON RESIN
WATER-OILREPELLENCY

IMPERMEABILITY / WATER COLUMN

ABOUT 25 CM








Fabric collection 2018

350 gr/m²

ACRYLIC



				
	A1 ECRU NATURAL COL. NATUR	70/80%	20/30%	85/89%
	T2 TERRACOTTA ZIEGELROT TERRACOTTA	> 90%	< 10%	100%
	T3 BORDEAUX	> 90%	< 10%	100%
	T6 GRIGIO TAUPE GREY TAUPE GRAU TAUPE GRIS TAUPE GRIJS TAUPE	> 90%	< 10%	100%
	T7 BIANCO WHITE BLANC WEISS	70/80%	20/30%	85/89%
	S1 NERO / BLACK SCHWARZ NOIRE NEGRO ZWART	> 90%	< 10%	100%

The above mentioned data are indicative, although provided by scientific measurements performed in certified laboratories.