

Exzenter Key Features

- ❖ Size range 1.5m to 4m manufactured in line with TUV standards
- ❖ Canopy offset (one third / two thirds), offering more space under the canopy for furniture
- ❖ Mast diameter 76mm with 3mm wall thickness
- ❖ Spokes 35mm x 20mm, support struts 30mm x 20mm
- ❖ All spokes reinforced with steel galvanised cores, as standard
- ❖ Spokes are tensioned, in order to keep the canopy taut and prolong the life of the membrane
- ❖ A removable hand crank with a bevel gear opens and closes the canopy
- ❖ Telescopic system, allowing closure over tables
- ❖ Frame made of durable F22 aluminium
- ❖ Frame colour: White (RAL9010), Anthracite (RAL 7016), Silver grey (RAL9006) or brown (RAL8019)
- ❖ European solution-dyed acrylic fabrics are used for the membranes, with a choice of around 40 colours. Optional fire-retardant PVC
- ❖ Integrated electrics with optional automatic cut off switch and heat-saver toggle button
- ❖ Standard wiring 6 core (1@ 4mm; 1@ 1.5mm), single phase
- ❖ Infra-red heaters options, allowing closure of the canopy without removing the heaters
- ❖ Optional LED lighting along the corner spokes
- ❖ Optional longer mast